



Engineered to **Redefine** **High Performance** **Industrial Printing**



GT4e Series

INDUSTRY VERTICALS

- Manufacturing
- Logistics
- Transportation
- Automobile
- Retail
- Government

APPLICATIONS

- Asset Tracking
- Warehouse Management System
- Logistic Tracking
- Retail Labelling
- Laboratory High-Resolution Labelling at 609dpi

RFID-ready ▶

No PC required ▶

Tri-interface port for various connectivity ▶

Large LCD display with graphical icons for user-friendly operation ▶

Easy-to-navigate menu options ▶

609dpi high resolution printing ▶



General Specifications

GT4e 

PRINTER MODEL		GT408e	GT412e	GT424e
PRINTING SPECIFICATIONS				
Print Method		Direct Thermal/Thermal Transfer		
Print Resolution		8 dots/mm (203dpi)	12 dots/mm (305dpi)	24 dots/mm (609dpi)
Max Print Speed		300mm/sec (12ips)	300mm/sec (12ips)	150mm/sec (6ips)
Max Print Area		Max (W x P): 104 x 2500mm (4.1" x 98.4")	Max (W x P): 104 x 1500mm (4.1" x 59.1")	Max (W x P): 104 x 400mm (4.1" x 15.7")
MEDIA SPECIFICATIONS				
Sensor Type		Reflective Sensor (for use with pre-printed marks), Adjustable See-Through Sensor (for die-cut labels with gaps)		
Media Thickness		Label thickness (With backing liner): 0.06 to 0.268 mm (0.002" to 0.01")		
Media Size		Width: 22 ~ 128mm (0.87" ~ 5.04"). With paper backing, 25 ~ 131mm (1" ~ 5.16") Pitch: 5 ~ 397mm (0.2" ~ 15.63"). With paper backing, 9 ~ 400mm (0.35" ~ 15.74")		
Media Roll Outer Diameter		Max external diameter 265mm (Paper core size: 1.5", 3", 4")		
Wind Direction		For Face-in and Face-out (Face-out is for linerless labels only)		
CONSUMABLES SPECIFICATIONS				
Ribbon Size	Width	Max: 128mm (5.04")		
	Length	Max: 450m		
	Winding Direction	Face-in and Face-out		
MEMORY/PROCESSING				
Main Memory		Flash-ROM: 6MB		
CPU		32 bit RISC		
COMMUNICATION INTERFACES				
Standard Interface		Plug In Interface Cards: RS-232C, High-speed RS-232C, USB, IEEE 1284, LAN, Centronics, RS-422/485 or Wireless LAN		
Optional		Mini LAN		
External Port		14-pin connector, 25-pin connector		
FONTS/BARCODE SYMBOLOGIES				
Standard Fonts		U, S, M, WB, WL, XU, XS, XM, XB, XL, OUTLINE, OCR-A, OCR-B		
TrueType Fonts		CG Times, CG Triumvirate		
Barcodes	1D Barcode	UPC-A/E, JAN/EAN, CODE 39, CODE 93, CODE 128, UCC/EAN 128, NW-7, Customer Barcode, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, BookLand, POSTNET, RSS-14		
	2D Barcode	QRCode (Chinese QR and Korean QR are individually operated), PDF 417 (Including Micro PDF417), MAXI Code, Data Matrix, Composite Symbology (Compatible with CC-A/B/C by UPC-A/E, JAN/EAN, CODE 39, CODE 128, RSS-14)		
	Character Rotation	0°, 90°, 180°, 270° rotation		
OPERATING & ENVIRONMENTAL				
Power Consumption		Max: 200VA / 200W (Standby: 62VA / 89W)		
Power Supply		Current AC 100 - 240 V		
Dimensions		(W x D x H): 271 x 455 x 305mm (10.67" x 17.9" x 12")		
Weight		Approx. 15kg		
Temperature / Humidity		Usage Environment: 0 ~ 40°C / 30 ~ 80%RH (Non condensing) Storage Environment: -5 ~ 60°C / 30 ~ 90%RH (Non condensing)		
ACCESSORIES & OPTIONS				
Special Options		Cutter, Dispense Unit (with Backing Paper Rewinder), Dispenser, Internal Rewinder, Linerless Kit, RFID Kit, Real Time Clock		
Memory Cartridge		Extended Flash Memory Board (24MB)		

Contact For a full list of all SATO offices, refer to www.satoworldwide.com

INTERNATIONAL HEADQUARTERS
SATO INTERNATIONAL PTE. LTD.
 438A Alexandra Road #05-01/04,
 Alexandra Technopark, Singapore 119967
 P: +65 6271 2122 F: +65 6271 2151
 E: sales@sato-int.com
 W: www.satoworldwide.com

AMERICAS
SATO INTERNATIONAL AMERICA, INC.
(Regional HQ)
 P: +1 704 644 1650
 E: satosales@satoamerica.com
 W: www.satoamerica.com

SATO AMERICA, INC.
 P: +1 704 644 1650
 E: satosales@satoamerica.com
 W: www.satoamerica.com

SATO LABELING SOLUTIONS AMERICA, INC.
 P: +1 630 771 4200
 E: sales@satolabeling.com
 W: www.satolabeling.com

EUROPE
SATO INTERNATIONAL EUROPE N.V.
(Regional HQ)
 P: +32 (0)2 788 80 00
 E: info@be.satoeurope.com
 W: www.satoeurope.com

SATO UK LTD.
 P: +44 (0) 1255 2400 00
 E: enquiries@satouk.com
 W: www.satouk.com

SATO LABELLING SOLUTIONS EUROPE GmbH
 P: +49 6272 9201 324
 E: info@de.satoeurope.com
 W: www.satoeurope.com/de

SATO POLSKA SP. Z O.O.
 P: +48 71 381 03 60
 E: info@pl.satoeurope.com
 W: www.satoeurope.com/pl

SATO FRANCE S.A.S.
 P: +33 (0)3 20 62 96 40
 E: info@fr.satoeurope.com
 W: www.satoeurope.com/fr

SATO IBERIA S.A.
 P: +34 902 333 341
 E: info@es.satoeurope.com
 W: www.satoeurope.com/es

ASIA PACIFIC AND OCEANIA
SATO INTERNATIONAL ASIA
PACIFIC PTE. LTD. (Regional HQ)
 P: +65 6271 5300
 E: sales@sato-int.com
 W: www.satoworldwide.com

SATO ASIA PACIFIC PTE. LTD.
 P: +65 6271 5300
 E: sales@satoasiapacific.com
 W: www.satoasiapacific.com

SATO AUTO-ID MALAYSIA SDN. BHD.
 P: +60 3 7620 8901
 E: sales@satosms.com.my
 W: www.satoasiapacific.com

SATO AUTO-ID (THAILAND)
CO., LTD.
 P: +662 736 4460
 E: sales@satothailand.co.th
 W: www.satoasiapacific.com

SATO SHANGHAI CO., LTD.
 P: +86 (021) 6306 8899
 E: sales@satochina.com
 W: www.satochina.com

SATO AUSTRALIA PTY LTD.
 P: +61 3 8814 5330
 E: sales@satoaustralia.com
 W: www.satoaustralia.com

SATO NEW ZEALAND LTD.
 P: +64 9 477 2222
 E: sales@satonewzealand.com
 W: www.satonewzealand.com